
























## ALUMINIUM ALLOY ANODES

<b>Specification Code</b>	AL-CHEM 1	
<b>Composition (weight %)</b>		
Iron	Fe	0.12 max.
Silicon	Si	0.05 - 0.15
Copper	Cu	0.003 max.
Zinc*	Zn	3.0 – 6.0
Indium	In	0.015 – 0.030 max.
Mercury	Hg	0.001 max.
Titanium	Ti	0.025 max.
Others each		0.02 max. (<0.1 total)
Aluminium*	Al	Remainder
Capacity- Amp.hr/kg	Typically 2760	

Anode Number		Overall Dimensions mm			Anode Body Dimensions mm			Net Weight (kg)	Gross Weight (kg)
		Length	Width	Height	Length	Width	Height		
AB-9C		300	150	30	160 mm Hole Centres for use with			3.4	3.7
AB-9E		300	150	50	160 mm Hole Centres for use with			4.7	5.0
AD35		160mm Dia		30	FOR USE WITH M10 STUDS			1.2	1.3
AD55		229mm Dia		25	FOR USE WITH M10 STUDS			2.6	2.85
AD56		100mm Dia		25	FOR USE WITH M10 STUDS			0.3	0.43
AD58		150mm Dia		35	FOR USE WITH M10 STUDS			0.8	0.9
AD60		380	125	25	320	125	25	2.6	2.9
AD72		563	102	64	457	102	64	5.0	6.0
AD72B		457	102	64	9" (229mm) Hole Centres for use with M16 studs			4.6	5.1
AD73		459	152	32	356	152	32	4.0	5.0

AD76		160	76	32	114	76	32	0.4	0.5
AD77		229	83	41	157	83	41	0.8	1.0
AD78		356	76	32	305	76	32	1.7	2.0
AD78B		305	76	32	8" (200mm) Hole Centres for use with M10 studs			1.5	1.85
AD79		229	83	41	8" (200mm) Hole Centres for use with M10 studs			1.3	1.5
AD80		405	152	32	305	152	32	3.0	4.0
AD82 120 - 40		913	202	38	813	102	38	7.5	9.0
MHA4X		390	110	40	290	110	40	4.0	4.5
MHA7X		590	110	50	490	110	50	7.0	8.0
MHAB7		600	80	60	12" (305mm) Hole Centres for use with M18 studs			7.0	8.0
MHA12X		920	110	50	820	110	50	12.0	13.5

**STUD FIXING TYPE M16 B FOR F.R.P./WOOD HULLS**



**FIXING TYPE M16 C FOR STEEL HULLS**

